

	Outline Vinduer A/S Fabriksvej 4 9640 Farsø, Danmark 2023
Facadeelementer – Beregnet til bygninger/ Facade elements – Intended for buildings Vinduer og døre i træ aluminium 3 lags/ Wood/ aluminium windows and doors 3 layer	
DoP ref. ID CE 23.7-5 EN 14351-1:2006 + A2:2016	
Termisk transmissionskoefficient (U-værdi)/ Thermal transmittance coefficient (U-value)	
1- fags oplukkeligt vindue/ Single window 1230 x 1480 mm med standard rude/ 1230 x 1480 mm with standard pane: 0,75* Rammedør/ Frame door	
1230 x 2180 mm med standard rude/ 1230 x 2180 mm with standard pane: 0,81*	
Strålingsegenskaber/ Radiation properties	
Standardrudens solfaktor (g-værdi)/ Standard pane's sun factor (g-value) 0,53	
Standardrudens lystransmission (Lt-værdi)/ Standard pane's light transmittance (Lt-value) 0,74	
Andre ydeevnebestemmelser/ Other performance measures	
Sikkerhedsudstyrs bæreevne (topvendevindue)/ Load-bearing capacity of safety equipment (top hung window) Bestået/ Passed	
Vindlast/ Wind load NPD	
Vandtæthed/ Watertightness NPD	
Akustisk ydeevne/ Acoustic performance NPD	
<i>NPD: no performance determined (ingen ydeevne fastlagt)</i>	

*Aktuelle termiske transmissionskoefficient (U-værdi) oplyses ved henvendelse til Outline Vinduer A/S

jf. EN 14351-1:2006 + A2:2016, Tabel E.1 note c. /

Current thermal transmission coefficient (U-value) can be obtained from Outline Vinduer A/S in accordance to EN 14351-1:2006 + A2:2016, Table E.1 note c.